Shuttle®

XPC SS56Gv3

Shuttle Mini Barebone PC System

Hot features, cool price!

The XPC SS56GV3 is loaded with features to help you discover, create, manage and fully digital media. Designed to bring the latest technologies to your desktop but still be affordable, this XPC offers fantastic support for all of your productivity, web and multimedia apps. Join the small form factor (SFF) revolution with Shuttle XPC SS56GV3.

The XPC SS56GV3 is an ideal: Desktop replacement, Office productivity, Home office and family computer, Student's dream workstation.

Feature Highlight

G chassis	• Silver aluminum chassis with light acrylic front face and blue stripe • Temperature controlled 92mm fan • Bays: 1x 5.25", 2x 3.5"
Chipset	• SiS 661FX / SiS 963L • Integrated graphics (64MB UMA)
CPU	• Sockel 478 supports 800/533MHz FSB • supports Pentium 4 (Prescott, Northwood) and Celeron processors
Slots	• 1 x AGP (8X) • 1 x PCI
Memory	• Supports DDR-400/333
Drive connectors	• 2x IDE ATA 133 • 1x floppy
other connectors	• 6-channel audio, SPDIF • Firewire, USB 2.0, Dual VGA • Fast Ethernet LAN
Power supply	• 200 Watt mini power supply
Application	• Home, Business

Article number: SS56GV3
Order number: PC-SS56GV3
UPC (see bar code)

8 11686 00068 6

© 2004 Shuttle Computer - Druckfehler und Irrtümer sowie Änderungen der Produktspezifikation vorbehalten.

Date: 24. Jan. 2005

Shuttle Computer Handels GmbH, Fritz-Strassmann-Strasse 5, D-25337 Elmshorn, Germany
Tel. +49 (0)4121 476-860 Fax. +49 (0)4121 476-900 Email: sales@spacewalker.de

Shuttle®

XPC SS56G v3

Shuttle Mini Barebone PC System

Specification

Chassis	G-type chassis made of aluminum, silver case cover and light acrylic front face with blue stripe storage bays: 1 x 5.25", 2 x 3.5" (1 internal) dimensions: 30 x 20 x 18.5 cm (LWH), weight: 2.85 kg net / 4.65 kg gross Slim-line and pre-installed cabling removes airflow impedance and makes installation a snap
Mainboard	Shuttle FS56, Shuttle form factor, proprietary design for SS56GV3 chipset: SiS 661FX / 963L Award V6.0PG BIOS, 4MBit flash memory with hardware monitoring and ACPI power management functions dimensions: 25.4 x 18.5 cm
Power supply	200 Watt mini PSU, supports 115/230V connectors: 20-pin ATX, 4-pin ATX12V
Processor support	Socket 478 supports Intel Pentium 4 and Celeron/Celeron-D processors at 800, 533 or 400 FSB supports Hyper-Threading, supports Northwood and Prescott CPU cores does not support Willamette (1.3~2.0 GHz, 256kB L2)
Processor cooling	Shuttle I.C.E. (Integrated Cooling Engine) advanced Heatpipe technology, linear fan control, 92mm cooling fan
Memory support	2 x 184 pin slots supports PC3200/2700/2100/1600 (DDR400/333/266/200) DDR SDRAM memory up to a total size of 2GB
Slots	1 x AGP 8X/4X (1,5V only) 1 x 32 Bit PCI (v2.2)
Graphics	SiS Real 256E (301C) 256-bit 3D engine shared Memory max. 64MB
6-channel audio	Realtek ALC650 5.1 channel audio controller AC97 v2.2 compiant, analog: line-out (6-ch), microphone, CD-in, AUX digital: optical SPDIF in and out
LAN Controller	Realtek 8100C Fast Ethernet network controller supports 10 / 100 MBit/s opteration
Firewire Controller	IEEE1394 Firewire controller VIA 6306, with 3 Firewire connectors (1x front and 2x rear) supports 400Mb/s, 200Mb/s, 100Mb/s data transfer rate
Drive connectors	2 x IDE ATA 133 drives 1 x floppy disk drive
Front Panel connectors	Microphone, Headphone (Line-out), Line-in 2x USB 2.0, Firewire (4 pol.)
Back Panel connectors	VGA connector for monitor, 2 x Firewire (6 pin), PS/2 for mouse and keyboard LAN (RJ45), 2 x USB 2.0, 2 x Serial ports (COM) 6-ch Audio line-out (2x rear/front, bass/center), optical SPDIF in and out Clear CMOS button, optional Wireless LAN module, optional parallel port
Other connectors	2 x USB 2.0 (total 6x) 2 x CDROM input 1 x AUX 1 x Infrared interface 3 x fan connectors

Date: 24. Jan. 2005

Shuttle Computer Handels GmbH, Fritz-Strassmann-Strasse 5, D-25337 Elmshorn, Germany
Tel. +49 (0)4121 476-860 Fax. +49 (0)4121 476-900 Email: sales@spacewalker.de